

**1145**  
High quality  
and low cost



**HIGHLIGHTS AT A GLANCE:**

- Compact 24-pin narrow carriage printer
- Up to 450 characters per second
- Ideal for front and back office applications
- Variety of interfaces
- Long life ribbon
- Small footprint



# 1145

The Tally Dascom 1145, is a 24 pin, 80 column serial dot matrix printer with USB interfaces as standard. Compact in size, the 1145 is perfect for industrial environments and front and back office applications where space is limited. With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

Amongst the lowest priced matrix printers available today the 1145 also offers a long life ribbon giving this printer very low running costs. For draft printing it's considerably less expensive running costs make it a viable alternative to low cost ink-jet printers.

## TECHNICAL DATA

<b>Print Speed</b>	Fastest Speed: 450 cps Character density 10 / 12 / 15 cpi <i>HS Draft</i> 450 / 360 / 450 cps <i>Draft</i> 300 / 360 / 450 cps <i>NLQ</i> 200 / 240 / 300 cps <i>LQ</i> 100 / 120 / 150 cps
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b>	296 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 8 lpi
<b>Print head Life</b>	400 million strokes
<b>Memory</b>	up to 256 kB
<b>Standard Connectivity</b>	USB 2.0
<b>Optional Connectivity</b>	Parallel IEEE 1284. Serial RS-232C, Ethernet (10/100)
<b>Emulation</b>	IBM ProPrinter 2390 Plus, Epson ESC P/2
<b>Fonts</b>	Draft, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
<b>Consumables</b>	Ribbon: 7 million characters
<b>Paper Handling</b>	Push tractor and friction
<b>Number of Copies</b>	1 original + 6 copies
<b>Paper Type</b>	Cut sheets, continuous forms, mult-part forms
<b>Paper Weight</b>	52 - 100 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 95 to 267 mm Length: 114 to 362 mm (Cut sheet); 114 to 558 mm (Fanfold)
<b>Physical Weight</b>	5 kg
<b>Physical Size</b>	369 x 283 x 130 mm (W x D x H)
<b>Acoustic</b>	57 dB(A)
<b>Power Voltage</b>	100-230 V - 50/60 Hz
<b>Power Consumption</b>	less then 1,4 Watt Sleep Mode
<b>Temperature</b>	+5° to +35° C; 10% to 80% humidity
<b>Workload</b>	6.000 pages per month
<b>MTBF</b>	12.000 hours
<b>Driver</b>	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022

### Configurations:

- **1145** Standard model with USB interface
- **1145 Par** Model with USB and parallel interface
- **1145 Eth** Model with USB and Ethernet interface
- **1145 Ser** Model with USB and serial interface

**DASCOM GB Ltd**  
Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

**DASCOM Europe GmbH**  
Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047